

TOOLS • SERVICE • TRAINING

Skidmore HS-100

- Portable Bolt-Tension Calibrator
- Test impact wrench output
- 170,000 lb Capacity
- Designed to test high-strength bolts from 3/4" to 1-1/2" in diameter
- Set production preload standards
- Both Regular and Short Bolts Kits



Skidmore HS-100

Minimum Bolt Length Chart

Bolt Diameter	Regular Adaptors	Short Bolt Adaptors
3/4"	2-1/2"	1-3/4"
7/8"	2-3/4"	2"
1"	3"	2-1/4"
1-1/8"	3-1/4"	2-1/2"
1-1/4"	3-1/2"	2-3/4"
*1-3/8"	3-3/4"	3-1/4"
1-1/2	4"	3-3/4"

^{*} Currently not in stock, but can procure if needed



**Spacer kits are available to increase grip on larger bolts



The Skidmore Model HS is a highly reliable direct-action hydraulic load cell instrument designed for use with high-strength bolts through 1-1/2 inch size. Direct dial readings to 170,000 pounds of bolt tension within 1% of accuracy show the preload delivered. Recommended minimum bolt tensions are plainly indicated on the gauge face. The Model HS can be clamped to a convenient column or bench. It is available with interchangeable bolt bushing and plate sets for each size bolt to be testing in a complete range through 1-1/2" bolt sizes.